

Data & Voice Cabling Guidelines

Columbus Zoo and Aquarium | Revised 12/08/2023

Introduction

This document is a guide. Due to the variety of buildings and projects across The Columbus Zoo and Aquarium, a variety of existing standards and practices are in use. For minor additions and changes to structured cabling, existing local standards/practices should be used. For new construction and major renovation, use the standards in this document.

Abbreviations used in this document

- Cat6 (or Cat6a): Category 6 or 6a UTP
- IDF: Intermediate Distribution Frame; also Distribution Equipment Room (DER)
- MDF: Main Distribution Frame; also Main Equipment Room (MER)
- TR: Technology Room (TR); also Technology Closet (TC)
- UTP: Unshielded twisted pair
- WAO: Work area outlets

Cabling standards

Horizontal cabling

Application	WAO termination	Cable	TR termination
Data, VoIP, and others not specified	TIA/EIA-568B Blue jack/keystone 12" slack	Blue Cat6 or Cat6a* UTP	TIA/EIA-568B 10' slack into cable management Cat6 or Cat6a modular (preferred) patch panel*** jack/keystone/snap-ins color match to WAO
CCTV/security cameras	TIA/EIA-568B Yellow jack/keystone 12" slack in plenum		
Analog telephony**	TIA/EIA-568B White jack/keystone 10-12" slack		
Wireless access points (APs)	TIA/EIA-568B Black jack/keystone 12" slack in plenum	Black Cat6 or Cat6a* UTP	
Audio/video patch connections local to one room	TIA/EIA-568B and Gray jack/keystone if RF45 termination	Gray Cat6 UTP	N/A

* As required for speed or distance

** **Analog telephony only where specifically scoped**

Risers, backbone, and TR interconnections

New projects, major renovation, or new TR buildouts should include the following minimum connections between the MDF, IDF(s) and buildings:

Application	Cable	TR termination
Data, VoIP, and others not specified	Aqua color jacket OM4, 6-pair Use only after consultation	LC into modular/snap-in fiber patch and tray with 12' slack
	Yellow color jack OS2, 2-pair Preferred	
Analog telephony*	25 pair copper trunk	110 block

* **Analog telephony only where specifically scoped**

Audio Visual cabling

New projects, major renovation, or new TR buildouts should include the following minimum connections between the MDF, IDF(s) and buildings:

Application	Cable	TR termination
Audio Visual	Aqua seal or UV block – stranded copper - depending on installation. Consultation required	In-wall boxes 2 1/8" deep Consultation required
	Black color – wire size per installation Consultation required	

Labeling standards

- Faceplates/ports/jacks at both WAO and TR ends should be typed or printed, permanent, and installed in accordance with manufacturer requirements (e.g. in labeling slots with clear protective covers). "P-Touch" or other consumer style labels are not acceptable.
- Labeling scheme: TR (if multiple) Rack (#) – Patch Panel (alpha) – Jack (#)
For example, the 10th floor west IDF, rack 1, panel B, jack 16 would be: **10W 01-B-16**
Single Floor building would not include floor number.
- Provide temporary labeling on cable jackets for use during pulling and installation.

Additional guidelines

- In-wall installation is always preferred over surface-mount.
- Install in wet/humid should be encased in schedule 40 conduit.

- Install where animals (mice/racoons/opossum/etc.) may come into contact should be encased in schedule 40 conduit.
- AV and network cabling will be in separate conduits.
- Match wall plates, surface block/biscuit jack, and surface raceway products to existing room or facility standards (white preferred).
- Comply with TIA-568 and TIA-569 standards for cabling, pathway, and EMI separation practices. Use plenum-rated cable.
- Conduct testing and certification according to TIA/EIA standards and provide documentation of satisfactory results.
- Panduit mini-con hardware is preferred.
Corning for fiber optic termination hardware
- All terminations in the cabinet will be into Panduit min-con patch panel.
- Installers must present proof of Panduit or Corning certifications for all installs.
- Indoor plenum for all office buildings, outdoor for all other locations.